

Technical drawing of a rectangular structure, likely a wall or partition, showing dimensions and labels.

The drawing includes the following dimensions and labels:

- Overall Width:** 1925
- Overall Height:** 500
- Top Section Height:** 125
- Bottom Section Height:** 100
- Right Section Width:** 600
- Left Section Width:** 500
- Labels:** A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z, AA, AB, AC, AD, AE, AF, AG, AH, AI, AJ, AK, AL, AM, AN, AO, AP, AQ, AR, AS, AT, AU, AV, AW, AX, AY, AZ, BA, BB, BC, BD, BE, BF, BG, BH, BI, BJ, BK, BL, BM, BN, BO, BP, BQ, BR, BS, BT, BU, BV, BW, BX, BY, BZ, CA, CB, CC, CD, CE, CF, CG, CH, CI, CJ, CK, CL, CM, CN, CO, CP, CQ, CR, CS, CT, CU, CV, CW, CX, CY, CZ, DA, DB, DC, DD, DE, DF, DG, DH, DI, DJ, DK, DL, DM, DN, DO, DP, DQ, DR, DS, DT, DU, DV, DW, DX, DY, DZ, EA, EB, EC, ED, EE, EF, EG, EH, EI, EJ, EK, EL, EM, EN, EO, EP, EQ, ER, ES, ET, EU, EV, EW, EX, EY, EZ, FA, FB, FC, FD, FE, FF, FG, FH, FI, FJ, FK, FL, FM, FN, FO, FP, FQ, FR, FS, FT, FU, FV, FW, FX, FY, FZ, GA, GB, GC, GD, GE, GF, GG, GH, GI, GJ, GK, GL, GM, GN, GO, GP, GQ, GR, GS, GT, GU, GV, GW, GX, GY, GZ, HA, HB, HC, HD, HE, HF, HG, HH, HI, HJ, HK, HL, HM, HN, HO, HP, HQ, HR, HS, HT, HU, HV, HW, HX, HY, HZ, IA, IB, IC, ID, IE, IF, IG, IH, II, IJ, IK, IL, IM, IN, IO, IP, IQ, IR, IS, IT, IU, IV, IW, IX, IY, IZ, JA, JB, JC, JD, JE, JF, JG, JH, JI, JJ, JK, JL, JM, JN, JO, JP, JQ, JR, JS, JT, JU, JV, JW, JX, JY, JZ, KA, KB, KC, KD, KE, KF, KG, KH, KI, KJ, KK, KL, KM, KN, KO, KP, KQ, KR, KS, KT, KU, KV, KW, KX, KY, KZ, LA, LB, LC, LD, LE, LF, LG, LH, LI, LJ, LK, LL, LM, LN, LO, LP, LQ, LR, LS, LT, LU, LV, LW, LX, LY, LZ, MA, MB, MC, MD, ME, MF, MG, MH, MI, MJ, MK, ML, MM, MN, MO, MP, MQ, MR, MS, MT, MU, MV, MW, MX, MY, MZ, NA, NB, NC, ND, NE, NF, NG, NH, NI, NJ, NK, NL, NM, NN, NO, NP, NQ, NR, NS, NT, NU, NV, NW, NX, NY, NZ, OA, OB, OC, OD, OE, OF, OG, OH, OI, OJ, OK, OL, OM, ON, OO, OP, OQ, OR, OS, OT, OU, OV, OW, OX, OY, OZ, PA, PB, PC, PD, PE, PF, PG, PH, PI, PJ, PK, PL, PM, PN, PO, PP, PQ, PR, PS, PT, PU, PV, PW, PX, PY, PZ, QA, QB, QC, QD, QE, QF, QG, QH, QI, QJ, QK, QL, QM, QN, QO, QP, QQ, QR, QS, QT, QU, QV, QW, QX, QY, QZ, RA, RB, RC, RD, RE, RF, RG, RH, RI, RJ, RK, RL, RM, RN, RO, RP, RQ, RR, RS, RT, RU, RV, RW, RX, RY, RZ, SA, SB, SC, SD, SE, SF, SG, SH, SI, SJ, SK, SL, SM, SN, SO, SP, SQ, SR, SS, ST, SU, SV, SW, SX, SY, SZ, TA, TB, TC, TD, TE, TF, TG, TH, TI, TJ, TK, TL, TM, TN, TO, TP, TQ, TR, TS, TT, TU, TV, TW, TX, TY, TZ, UA, UB, UC, UD, UE, UF, UG, UH, UI, UJ, UK, UL, UM, UN, UO, UP, UQ, UR, US, UT, UY, UZ, VA, VB, VC, VD, VE, VF, VG, VH, VI, VJ, VK, VL, VM, VN, VO, VP, VQ, VR, VS, VT, VU, VV, VW, VX, VY, VZ, WA, WB, WC, WD, WE, WF, WG, WH, WI, WJ, WK, WL, WM, WN, WO, WP, WQ, WR, WS, WT, WU, WV, WW, WX, WY, WZ, XA, XB, XC, XD, XE, XF, XG, XH, XI, XJ, XK, XL, XM, XN, XO, XP, XQ, XR, XS, XT, XU, XV, XW, XX, XY, XZ, YA, YB, YC, YD, YE, YF, YG, YH, YI, YJ, YK, YL, YM, YN, YO, YP, YQ, YR, YS, YT, YU, YV, YW, YX, YY, YZ, ZA, ZB, ZC, ZD, ZE, ZF, ZG, ZH, ZI, ZJ, ZK, ZL, ZM, ZN, ZO, ZP, ZQ, ZR, ZS, ZT, ZU, ZV, ZW, ZX, ZY, ZZ.

QUANTIDADES			
MUROS	EXTENSÃO (M)	ÁREA (M2)	VOLUME (M3)
SEÇÃO A-A	25,75	5,25	135,18
SEÇÃO B-B	7,00	5,75	40,25
TOTAL			175,43

Technical drawing of a cross-section (Corte A-A) of a stone wall. The wall has a total height of 300 units and a base width of 200 units. The top width is 50 units. The wall is filled with a stone pattern. A 25-degree slope is indicated on the right side. The drawing includes dimensions for the wall's height, width, and the slope angle.

Technical drawing of a drainage system for a roof or floor. The drawing shows a cross-section of a sloped surface with a drainage channel. The channel is labeled "DRENO DE BRITA 9.5MM" and "DRENO DE BRITA 19MM". The slope is indicated as "25°" and "25 x 75". The channel is shown with a cross-section of "e50 i=0.5%".

1. MURO EM CONCRETO CICLÓPICO $f_{ck}=30$ MPa E PEDRAS DE MÃO DE 30 CM
2. O ÂNGULO MÁXIMO DO TALUDE À MONTANTE NÃO PODERÁ ULTRAPASSAR 25°
3. O MACIÇO TERROSO A CONTER DEVERÁ SER COMPACTADO COM CONTROLE REFERENTE AO PROCTOR NORMAL, LANÇADO EM CAMADAS DE 30CM, COMPACTADO COM SOQUETE MANUAL, PLACA VIBRATÓRIA OU SAPO MECÂNICO, PARA OBTENÇÃO DE UM GRAU DE COMPACTAÇÃO MÍNIMO IGUAL A 95%.
4. AS DIMENSÕES E COTAS DEVERÃO SER CONFERIDAS COM O LEVANTAMENTO PLANIALTIMÉTRICO CADASTRAL
5. INSTALAR TELA DE BÍDM NA ENTRADA DOS BARBACANS
6. REALIZAR SONDAGEM À PERCUSSÃO COM BASE NO ENSAIO SPT (STANDARD PENETRATION TEST) E ABNT NBR 6484:2001, PARA CONFIRMAÇÃO DA CAPACIDADE RESISTENTE DO SOLO NA CAMADA DE APOIO. ESTE PROJETO FOI ELABORADO PARA UMA TENSÃO ADMISSÍVEL NESTA CAMADA, IGUAL A 1,00 kg/cm2.

[illegible]



Emitido em 28/05/2020

PROJETO Nº 74/2020 - SUMAI/UFBA (12.01.08)

(Nº do Protocolo: NÃO PROTOCOLADO)

(Assinado eletronicamente em 18/06/2020 20:34)

MARUCHA DA SILVA ALVES DE JESUS

SECRETARIO EXECUTIVO

2250058

Para verificar a autenticidade deste documento entre em <https://sipac.ufba.br/documentos/> informando seu número:
74, ano: **2020**, tipo: **PROJETO**, data de emissão: **18/06/2020** e o código de verificação: **02bf0bb1e6**